



Pro300 Specification Sheet

MODEL	PRO300-032
FACTORY PRESET MINUTES	
BACKWASH: MINUTES	8
GALLONS	13.6
BRINE/RINSE MINUTES	60.0
GALLONS	16.2
FINAL RINSE : MINUTES	4.0
GALLONS	6.8
<u>GALLONS@35PSI, INCLUDES BRINE MAKE UP.</u>	36.6
ReFill - Pounds of Salt	
LOW SALT MINUTES	3.5
POUNDS	5
MEDIUM SALT MINUTES	6.7
POUNDS	10
HIGH SALT MINUTES	10
POUNDS	15
CAPACITY IN GRAINS	
LOW SALT	20,000
MEDIUM SALT	28,060
HIGH SALT	32,310
GRAINS OF HARDNESS REDUCED PER POUND OF SALT AT FACTORY SETTING	4000
Service Flow Rate	
FLOW RATE AT 10 PSI	10.1
FLOW RATE AT 15 PSI	13.0
OTHER DATA	
RESIN, CUBIC FOOT	1
HAC (CU FT)	NA
MINERAL TANK DIMENSION*	948
BRINE TANK DIMENSION	1833
DRAIN LINE FLOW CONTROL GPM	1.7
BRINE LINE FLOW CONTROL GPM	0.5
INJECTOR, COLOR	RED

Factory Settings are in Bold

System conforms to NSF/ANSI 44 for specific performance claims. Efficiency is valid only at stated salt dosage. Efficiency is measured by laboratory test described in NSF/ANSI44. This represents the maximum possible efficiency the system can achieve; The operational efficiency is the actual efficiency achieved after the system has been installed. The operational efficiency is typically less than the tested efficiency due to individual application factors including water hardness, water usage and other contaminants that reduce softener capacity. These efficiency-rated softeners are Demand-Initiated Regenerating (DIR) Softeners which comply with specific performance specifications intended to minimize the amount of brine and water used in operation.

If application demands 1 gpg or less in service flow at peak flows, may need to add safety factor to programming capacity.

Hellenbrand products are not for sale or distribution into the State of California effective 8/31/18.