



Pro305 High Efficiency Specifications

Model #	PRO305-032	PRO305-042	PRO305-59
---------	------------	------------	-----------

Regeneration Gallons on Factory Settings @ 35 psi	24.1	33.5	45.7
---	------	------	------

Capacity ¹	Grains	Grains	Grains
High Efficiency Salting (5400gr/lb) ²	17,820	23,700	32,940
Low Salting (5200 grains/lb)	20,800	27,664	38,480

Service Flow Rates	GPM	GPM	GPM
Service Flow @ 10 psi	5.5	6.8	7.8
Peak Flow @ 15 psi	7.9	9	10.4
Resin Tank Size	8x44	9x48	10x54
Recommended Brine Tank	18x33	18x33	18x33
Brine Line Size	3/8"	3/8"	3/8"

Factory Settings at Low Salting, 5200 grains/lb.

1. System conforms to ANSI/NSF 44 performance claims as verified and substantiated by test data.

2. High efficiency salting is maximum efficiency system can achieve, efficiency is only valid at stated salt dosage.

The operational efficiency may be less than the tested efficiency due to individual application factors such as water hardness, TDS, water usage or other contaminants in water supply that may reduce softener capacity.

Operating Parameters:

Up to 40 gpg hardness

Up to 0.5 ppm Iron

Upflow high efficiency water softeners are intended for clean water such as municipal supplies or well water applications with proper pre-treatment.

Hellenbrand products are not for sale or distribution into the State of California effective 8/31/18.