



PROFICIENT PR0300 HIGH BACKWASH SOFTENER SPECIFICATIONS

MODEL	PRO300-24-HBKW	PRO300-32-HBKW
FACTORY PRESET MINUTES		
BACKWASH: MINUTES	8.0	8.0
BRINE: MINUTES	60.0	60.0
2ND BACKWASH: MINUTES	8.0	8.0
RINSE: MINUTES	4.0	4.0
ReFill - Pounds of Salt		
Medium Salting- 10 lbs/Ft.3	7.5	10
High Salting - 15 lbs/Ft.3	11.25	15
Capacity - Grains		
Medium Salt	21,040	28,060
High Salt	24,320	32,310
Water Usage* (Gallons)		
	84	108
Service Flow Rate		
Flow Rate @ 10 psi	10.1	10.5
Flow Rate @ 15 psi	13	14.1
Other Data		
Resin, Cubic Feet	0.75	1
Mineral Tank Dimension	9x48	10x54
Brine Tank Dimension	18x33	18x33
Drain Line Flow Control	3.2	4.2
Brine Line Flow Control	0.5	0.5
Injector, color	C - Violet	D - Red

*Regeneration Water Usage at Factory Settings @50 psi & includes brine make-up-water.

Factory Settings in Bold

These specially engineered water softeners are designed to reduce iron as well as hardness. Iron MUST be in dissolved form to be effectively reduced. Prefilters such as sediment filters are recommended to trap any oxidized iron.

Hellenbrand products are not for sale or distribution into the State of California effective 8/31/18.